

DATA SHEET/Datenblatt

Connector UHF crimp

part.-no. 7400

UHF Stecker crimp

Art. Nr. 7400



Description

Coaxial connector UHF male

Beschreibung

Koaxial UHF-Stecker

Mechanical characteristics

cables
assembly link:
centre conductor
outer conductor
couplung tourque

Mechanische Eigenschaften

Kabel
Link für die Montageanleitung:
Innenleiter
Ausenleiter
Kupplugsdrehmoment

Aircell®7
to crimp / zu crimpen
to crimp / zum crimpen
4-6 Nm

Components

pin
body and other metal parts
insulator
gasket

Bauteile

Pin
Körper und andere Metallteile
Isolierung
Dichtung

CuZn39Pb3 / gold plated
CuZn39Pb3 Ni plated
TEFLON® (PTFE)
silicone rubber

Electrical characteristics

impedance
Frequency range
Contact resistance
working voltage
insulation resistance

Elektrische Eigenschaften

Wellenwiderstand
Frequenzbereich
Durchgangswiderstand
Betriebsspannung
Isolationswiderstand

50Ω
bis 200 MHz
≤ 0,05 dB
≤ 750 V RMS
≥ 5GΩ

Environmental

RoHS compliant
protection class
operating temperature

Umgebung

RoHS konform
Schutzklasse
Betriebstemperatur

2002/95/EC
IP (IEC 60529)
-30°C/+100°C

