## KENWOOD

UHF FM TRANSCEIVER



- **KNB-71L** Li-ion Battery (3.8 V/1,430 mAh)
- KSC-44CR Fast Charger
- KSC-44SL AC adapter single
- KBH-20 Spring Action Belt Clip
- Owner's Manual

**OPTION** 

\*Available later







**KBH-20** Spring Action Belt Clip



KSC-44SL AC Adapter Single



KSC-44ML AC Adapter Multiple



KNB-71L Li-ion Battery (3.8 V/1,430 mAh)



**KHS-33** Earbud In-line PTT Headset (Single Pin Jack)




**KHS-34** C-Ring In-line PTT Headset (Single Pin Jack)

#### **SPECIFICATIONS**

NODEL	PKT-23E			
GENERAL				
Frequency Range	446.0 to 446.1 MHz			
Number of Channels	Max. 8			
Channel Spacing (Narrow)	12.5 KHz			
Battery Voltage	3.8 V DC ± 10 %			
Battery Life (5-5-90)*	Approx. 15 hrs			
Frequency Stability	+/-2.5 ppm			
Dimensions (Excluding antenna )	W46.0 x H85.0 x D21.0 mm			
Weight with battery	Approx. 110 g			
RECEIVER				
Sensitivity (Narrow) EN 20dB SINAD	-7.0 dBμV			
Selectivity (Narrow)	60 dB			
Intermodulation Distortion (Narrow)	60 dB			
Audio Distortion	Less than 5 %			
Audio Output (Internal)	300 mW/4 Ω			
Audio Output (External)	2 mW/32 Ω			
TRANSMITTER				
RF Power Output	ERP 500 mW			
Spurious Response	-36 dBm ≤ 1 GHz, -30 dBm > 1 GHz			
FM Hum & Noise (Narrow)	50 dB			
Modulation Distortion	Less than 5 %			
Type of Emission	8K50F3E			

<sup>\*</sup>Based upon 5 % transmit / 5 % receive / 90 % standby (standard duty cycle)

### JVCKENWOOD U.K. Limited





The PKT-23. An easy-to-use, license-free PMR446 UHF FM transceiver. Thin, lightweight and durable. Compliant with IP54 and 11 US MIL-STD standards.

### **Small**

At **110 g**, it is the smallest & lightest 2-Way Radio from KENWOOD.

### **Simple**

Simple and license-free operation in an all-in-one package ready for immediate use.

### **Tough**

Complies with **IP54** (dust/water resistant) and durability meeting or exceeding **MIL-STD** 810 C/D/E/F/G **11 items**.

### Powerful

**500 mWatts** Transmit Power. Up to **15 hours** of operation. (5-5-90; battery saver ON)







### **Built Business Tough**

#### Meets MIL-STD and IP54

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/ I	50 0.2/ I, II	500.3/ I, II	500.4/ I, II	500.5/ I, II
High Temperature	501.1/ I, II	501.2/ I, II	501.3/ I, II	501.4/ I, II	501.5/ I, II
Low Temperature	502.1/ I	502.2/ I, II	502.3/ I, II	502.4/ I, II	502.5/ I, II
Temperature Shock	503.1/ I	503.2/1	503.3/ I	503.4/ I, II	503.5/ I
Solar Radiation	505.1/ I	505.2/1	505.3/ I	505.4/ I	505.5/ I
Rain	506.1/ I, II	506.2/ I, II	506.3/ I, II	506.4/ I, III	506.5/ I, III
Humidity	507.1/ I, II	507.2/ II, III	507.3/ II, III	507.4	507.5/ II
Salt Fog	509.1/ I	509.2/1	509.3/ I	509.4	509.5
Dust	510.1/ I	510.2/ I	510.3/ I	510.4/ I, III	510.5/ I
Vibration	514.2/ VIII, X	514.3/ I	514.4/ I	514.5/ I	514.6/ I
Shock	516.2/ I, II, V	516.3/ I, IV	516.4/ I, IV	516.5/ I, IV	516.6/ I, IV
International Protection Standard					
Duet & Water Protection		ID5/I			

#### **Built-in 3.5D Jack**

Connect the KHS-33 or KHS-34 headphone for better use in noisy environments or for private conversations.



\*Headphones and earphones are not supplied with the unit.

#### **Built-in VOX**

Built-in VOX allows hand free operation which automatically starts transmission in response to your voice when using an external microphone.

### **Equipped with Micro USB** terminal

The standard micro USB port means a smart phone charger can also be used to charge the PKT-23.



### **Self Programing**

User selectable channel frequencies, QT tones, and DQT codes without using an FPU(programming software).





### **Easy Communication**

### **Light Weight and Simple Operation**

Fitting in the palm of your hand, the PKT-23 is easy to take anywhere your staff needs to go. At only 110 g, it can fit comfortably in a pocket or attached with the included belt clip. The front panel button layout makes the PKT-23 easy to operate.



### 500 mW Transmit Power with Up to 15 Hours of Operation

The PKT-23 offers 500 mWatts of power, for direct radio-to-radio communication on the same frequency. The built-in 1,430 mAh lithium-ion battery provides up to 15 hours of use.

Battery life		
Battery life (5-5-90 duty cycle)	Saver on: 15 hours	
	Saver off: 11 hours	
Battery charging time	2 hours	

#### 8 Channels with Voice Guide

The PKT-23 provides up to 8 channels, allowing you to assign channels to specific team members. The Voice Guide alerts you when you change channels.



#### **Calling Alert**

You are alerted to an incoming call by the flashing LED light and a beep.



#### **Multi-coloured LED**

Blinking LED lights in 3 colours indicate the PKT-23's transmission status and low battery status.







# ProTalk LT UHF FM TRANSCEIVER PKT-23

PMR446 License Free Radio

#### Actual size

W: 46 mm

H: 85 mm D: 21 mm

\*Excluding antenna.