

VX-450 Series

VHF/UHF Portable Radios

SPECIFICATION SHEET

Durable On-the-Job Responsiveness

The industrial grade VX-450 Series maximises worker uptime with expanded safety applications and convenient built-in features designed for heavy duty use.

Monitor Worker Safety

As with all Vertex Standard radios, the VX-450 series includes built-in **Emergency and Lone Worker alerts**. Emergency notification is user-initiated with a press of a button for the radio to switch to a designated channel and send an alert for help. Lone Worker mode is a built-in timer that requires the user to reset at a predetermined interval. If not reset, the radio automatically switches to Emergency mode to alert help.

When constant contact is required at all times, Vertex Standard's exclusive **Auto-Range Transpond System II (ARTS II™)** is included to inform the user that other ARTS II - equipped radios are within communication range.

No two job sites are alike and the optional **Man Down function** (with DVS-9 unit) is programmable to monitor a variety of worker timed safety scenarios vertically and horizontally as well as worker degree of motion. Adjusting the settings of the 3-axis sensor adapts the radio to each distinct work environment to monitor movement.

Solid Build for Extreme Environments

The VX-450 Series withstands job site abuse meeting military standards for ruggedness and meets the IP57 ingress protection standard where water does not harm the radio when submersed to a depth of 1 metre for up to 30 minutes.

Audio and Voice Responsiveness

Features 700 mWV **loud audio output** ideal for noisy work environments.

Includes **Multi-lingual Channel Announcement** which loudly speaks the channel description to simplify changing channels. Alternatively record your own announcements to allow easier navigation.

Features **Voice Activation (VOX)** when used with MH-81A4B headset that enables users to transmit voice without pressing the Push To Talk button for hands-free operation.

Record and store up to 120 seconds of voice messages using the optional DVS-8 **Voice Storage** unit.

Built-in Selective Signaling Modes for Greater Flexibility


Includes MDC-1200® encode/decode along with DTMF, 2-tone and 5-tone encode/decode; providing selective radio calling and efficiency in supporting a variety of discrete communications needs.

Large Group Communications Made Easy to Manage

Both the VX-459 and VX-454 radios have a massive **512-channel capacity** and 32 groups to easily manage a variety of calls at the most complex job site or plant operation. The VX-459 also includes **Direct Channel Entry** to punch in the channel desired from the keypad for fast navigation.

The Vertex Standard Difference

Our number one goal is achieving superior customer satisfaction by delivering products and services that exceed your expectations. Vertex Standard radios are built to last and are backed by a comprehensive warranty. Ask your Dealer for more details.



Top



VX-459

VX-451

VX-454

109 x 58 x 34 mm



VX-450 Series

VHF/UHF Portable Radios

 Vertex Standard

SPECIFICATION SHEET

www.vertex-standard-emea.com



Additional Features

- ▶ Nine programmable keys (VX-459)
- ▶ Seven programmable keys (VX-454)
- ▶ Three programmable keys (VX-451)
- ▶ 8-Character alphanumeric display (VX-454/459)
- ▶ Voice inversion encryption
- ▶ Manual on/off encryption activation
- ▶ RX/TX Battery power save
- ▶ DTMF ANI
- ▶ DTMF Speed dial
- ▶ DTMF Paging
- ▶ CTCSS / DCS Encode and Decode
- ▶ Stun/kill/revive (5-tone)
- ▶ 2 tone encode/decode
- ▶ 5 tone encode/decode
- ▶ MDC 1200® encode/decode
- ▶ Compander
- ▶ Clear voice
- ▶ Whisper
- ▶ Minimum volume control
- ▶ Manual squelch adjustment
- ▶ BCLO, BTLO and TOT Functions
- ▶ Programmable LED color alert
- ▶ Priority scan
- ▶ Dual Watch scan
- ▶ Follow-me scan
- ▶ Talk Around scan
- ▶ Radio-to-radio cloning
- ▶ Audible channel announcement (customisable)

Accessories

- ▶ MH-360S: Compact speaker microphone
- ▶ MH-37A4B: Earpiece microphone
- ▶ MH-450S: Speaker microphone
- ▶ MH-45B4B: Noise cancelling speaker microphone
- ▶ MH-81A4B: Over-the-head light duty VOX headset
- ▶ VH-110S: Over-the-head heavy duty dual-muff headset
- ▶ VH-115S: Behind-the-head headset w/boom mic
- ▶ VH-215S: Over-the-head single-muff headset
- ▶ VH-120S: Earpiece mic w/palm PTT switch
- ▶ VH-130S: Earpiece w/palm mic and PTT switch
- ▶ FNB-V113LI: 2400 mAh Li-Ion battery
- ▶ FNB-V134LI-UNI: 2300 mAh Li-Ion
- ▶ FNB-V133LI-UNI: 1380 mAh Li-Ion
- ▶ CSS-450 Channel selector stopper
- ▶ VAC-UNI: Single Unit charger
- ▶ VAC-6058: MUC -UNI 6 unit charger
- ▶ VAC-6450: 6 unit charger (FNB-112 LI, FNB-113 LI)
- ▶ CD-49: Desktop rapid charger (FNB-112 LI and FNB-113 LI)
- ▶ VCM-5: Vehicle Unit Charger (FNB-V134LI, FNB-V133LI)
- ▶ VCM-4: Vehicle charger mount (FNB-V113LI, FNB-V112LI)

Option Boards

- ▶ DVS-8: Digital voice storage unit
- ▶ DVS-9: Man down alert with digital voice storage
- ▶ FVP-44 Rolling code Encryption Unit

VX-4500/4600 Series Specifications

	VHF	UHF
General Specification		
Frequency Range	136 - 174 MHz	300 - 340 MHz* 350 - 390 MHz* 403 - 470 MHz 450 - 520 MHz*
Number of Channels and Groups	512 / 32 Groups (VX-459,VX-454) 32 / 2 Groups (VX-451)	
Power Supply Voltage	7.4V DC±10 %	
Channel Spacing	12.5 / 20 / 25 kHz	
PLL Steps	1.25 / 2.5 / 5 / 6.25 kHz	5 / 6.25 kHz
Battery Life (5-5-90 duty w/battery saver)	17.7 h (15.3 h w/o saver) 17.2 h (14.9 h w/o saver)	
2300 mAh Li-Ion: FNB-V134LI-UNI	11.2 h (10.1 h w/o saver)	10.8 h (11.9 h w/o saver)
1380 mAh Li-Ion: FNB-V133LI-UNI		
IP Rating	IP 57	
Operating Temperature Range	-20° C to +55° C	
Frequency Stability	±2.5 ppm	
RF Input-Output Impedance	50 Ohms	
Dimension (H x W x D)	109 x 58.5 x 35 mm (w/FNB-V133LI-UNI) 109 x 58.5 x 43 mm (w/FNB-V134LI-UNI)	
Weight (Approx.)	286 g (10 oz) (w/FNB-V133LI-UNI, Antenna, Belt Clip) 335 g (11.8 oz) (w/FNB-V134LI-UNI, Antenna, Belt Clip)	
Receiver Specification:		
Sensitivity 20dB SINAD	-2 dBuV	-2 dBuV
Adjacent Channel Selectivity	70 / 65 dB (25 kHz / 12.5 kHz)	
Hum and Noise	45 dB / 40 dB	
Intermodulation	70 dB / 65 dB	
Spurious and Image Rejection	65 dB	
Audio Output	700 mW (internal @ 16 Ohms, 5% THD) 500 mW (external @ 4 Ohms, 5% THD)	
Transmitter Specification:		
Output Power (Selectable)	5 / 2.5 / 1 / 0.25 Watt (selectable by channel)	
Modulation	16K0F3E, 11K0F3E Variable Reactance Modulation	
Maximum Deviation	±5.0 kHz / ±4.0 kHz / ±2.5 kHz	
Conducted Spurious Emissions	70 dB below carrier	
FM Hum and Noise	45 / 40 dB (25 kHz / 12.5 kHz)	
Audio Distortion	< 3 % @ 1 kHz	

Applicable MIL-STD

Standard	Methods/Procedures				
	MIL 810C	MIL 810D	MIL 810E	MIL 810F	MIL 810G
Low Pressure	500.1 / Procedure I	500.2 / Procedure I	500.3 / Procedure I	500.4 / Procedure I	500.4 / Procedure I, II
High Temperature	501.1 / Procedure I, II	501.2 / Procedure I, II	501.3 / Procedure I, II	501.4 / Procedure I, II	501.4 / Procedure I, II
Low Temperature	502.1 / Procedure I	502.2 / Procedure II	502.3 / Procedure II	502.4 / Procedure II	502.4 / Procedure II
Temperature Shock	503.1 / Procedure I	503.2 / Procedure I	503.3 / Procedure I	503.4 / Procedure I	-
Solar Radiation	505.1 / Procedure I	505.2 / Procedure II	505.3 / Procedure II	505.4 / Procedure I,II	-
Rain	506.1 / Procedure I, II	506.2 / Procedure II	506.3 / Procedure II	506.4 / Procedure III	506.5 Procedure III 506.2 Procedure I
Humidity	507.1 / Procedure I, II	-	507.3 / Procedure II	-	507.4 / Procedure I
Salt spray/Fog	509.1 / Procedure I	509.2 / Procedure I	509.3 / Procedure I	509.4 / Procedure I	509.4 / Procedure I
Dust	510.1 / Procedure I	510.2 / Procedure I	-	510.4 / Procedure I, III	510.4 / Procedure I, III
Vibration	514.2 / Procedure VIII, X	-	-	-	-
Shock	516.2 / Procedure IV	-	516.4 / Procedure I	516.5 / Procedure I	516.5 / Procedure I
Transit Drop	-	-	-	-	516.5 / Procedure IV
Blowing Rain	-	-	-	-	506.2 / Procedure I

* Non-CE models only.

Specifications are subject to change without notice or obligation.

Vertex Standard is a trademark of Vertex Standard LMR, Inc. All other trademarks are the property of their respective owners. © 2014 Vertex Standard LMR, Inc. All rights reserved.

CESS_450_12/2014

Designed and engineered in Japan.